

elevate

wallcovering

TECHNICAL SPECIFICATIONS

FIRE RATING

elevate wallcoverings are all Class A fire rated in accordance with ASTM-E84 tunnel test.

RECYCLE CONTENT

elevate wallcoverings are paper backed and most use recycled paper backing. For the recycle content, see the pattern page content list where the percentage is noted.

LOW-EMMITING MATERIALS

There are no chemical additives in **elevate wallcovering** products. They are free of PVC, Chlorine, Heavy Metals and Urea Formaldehyde. Only water based inks and coatings are used on these products. Other attributes of these products are that they are antibacterial, low emitting materials and safely disposable. These products have a top coat of polyvinyl acetate for washability. Further environmental information is available upon request.

CERTIFIED WOOD

All our Wallcoverings with wood pulp and cellulose come from certified sources which include Smart Wood, Rainforest Alliance and SGS. The sustainable forestry techniques used to harvest the wood pulp make it a renewable resource. Under the **Forest Stewardship Council (FSC)**, the third party organizations listed above certify that forest management practices of our sources adhere to strict environmental and socioeconomic standards. Each of these sources has a Chain -of - Custody Certificate number (available upon request).

THIRD PARTY VERIFICATION

In addition to high environmental standards for our products content, our Mills use management practices set forth by the **International Standards Organization (ISO)** for manufacturing our products. The ISO 14001 and ISO 9911 2000 certification confirms that our Mills operate in an environmentally sustainable manner. It further assures our Mill's employees that they are working for a socially and environmentally responsible Organization. It also provides assurance to the A and D Community and regulatory agencies that our Mills complies with **Global Environmental Regulations**.

WARRANTY:

elevate wallcovering guarantees that this product will perform in accordance with accepted industry standards when used under normal conditions and for the purpose intended for a period of one year from date of purchase.

INSTALLATION GUIDELINES:

Hanging instructions are supplied with each shipment. For best results, it is recommended that a qualified TEXTILE wallcovering installer be employed. **elevate wallcoverings** are manufactured to the highest quality standards possible. As with all natural fiber materials, irregularities in weave and coloration are normal occurrences that enhance the hand-made appearance. This provides a look that cannot be duplicated by conventional machine made wallcoverings.

MAINTENANCE:

General maintenance can be achieved with periodic dusting or vacuuming of this product. All stains should be treated as soon as possible with clean water, by using a soft cloth (white) or sponge. For most stains a commonly used water base household products can be used, being careful not to flood the surface. Abrasive rubbing of spots should be avoided so that discoloration cannot appear. More care should be taken in cleaning any dark colors because of the possibility of causing "light marks". Test first in an inconspicuous area.

www.elevatewallcovering.com