

HANGING SUGGESTIONS:

1. Wall must be clean, smooth and sealed.
2. A heavy-duty clear adhesive should be used.
3. For best results, environmental temperature should not be below 55 degrees F or exceed 75 degrees F.
4. Paper-backed fiber materials require 5-8 minutes booking time (pasted sheets folded together) to allow expanding of materials. Care must be taken not to crease the wallcovering while booking.
5. For better joint, we suggest that the material be double cut. When double cutting, we recommend that 2-3 inch wide strips be placed behind the seam to stop scoring or cutting into wall. After double cutting, peel out the strip, pat down the seam and wash off excess adhesive with a wet sponge and clean water, then clean with a dry towel. Lightly roll seams to set in place. Hard rolling can cause a sheen on the seam.
6. Use strips in the exact order as they are cut from roll. Fill in over doors and windows with strips cut in consecutive order from the roll. Hang only 1-2 strips at a time.
7. Smooth material with soft bristle brush to eliminate air bubbles and ensure good adhesion.

WASHABILITY:

This material has been treated with a washable finish to allow the washing of stains. Stains should be treated as soon as possible with clean water, by using a soft cloth or sponge. For harder stains a mild detergent solution of warm water can be used. Be careful not to flood the surface. Avoid hard rubbing of spots, so that discoloration will not occur. More care should be taken in cleaning any dark colors to avoid "light marks" on the material.